




INKA CAT6 U PE 1 km Black

Article number : 695020756

Product categorie: UTP Cable



INKA CAT6 U PE 1 KM BLACK

Premium grade CAT6 UTP network cable. Easy to connect to RJ45 connectors such as the CAT RJ45+T from Hirschmann Multimedia. This UTP network cable is suitable for use in Ethernet networks, xDSL, ISDN, LAN, FTTH, Video and PoE (Power over Ethernet). Equip your products with a Gigabit internet connection: network switches, desktop computers, VOIP, IP cameras, routers, access points, etc. You can find installation instructions on www.install-your-data.net.

Certificates

Gigabit
ethernet

Easy
install

Low
Loss

CAT 6

Properties



Include

Instruction video

Instruction card

Article dimensions

Length:
Width:
Height:
Weight:

540 mm
540 mm
250 mm
43 kg



Product specifications

Mechanical specifications

Conductor material :	Bare copper wire
Conductor diameter (mm \ AWG) :	0.55 \ 23
Cross separator material :	PE
Insulation diameter (mm) :	0.96
Screen material :	N/A
Sheath material :	PE
Sheath diameter (mm) :	6.0
Cable color :	Black
Crush Resistance (N/10 cm) :	1000
Min. bending radius (once) :	30
Min bending diameter (multi) :	60
UV Resistant (Y/N) :	Y
Halogen free (acc. EN 60754-1/2) (Y/N) :	N
Under ground use (Y/N) :	Y
Armoured (Y/N) :	N
Length (m) :	1000

Electrical specifications

Impedance (Ω) :	100
DC resistance (Ω /km) :	85
Resistance Unbalance (%) :	2
Mutual Capacitance (pF/m) :	50
Capacitance unbalance (pF/km) :	1600
Coupling attenuation :	Type III
Velocity of propagation (%) :	67 - 69
Propagation Delay (ns/100 m) :	537
Skew (ns/100 m) :	45
Testing Voltage (V) :	1000
Operating voltage (V) :	72

Environmental specifications

Temperature Range ($^{\circ}$ C) :	-20 to +60
-------------------------------------	------------

Approvals

Year of first CE-marking :	2020
Reaction-to-fire class according to EN 13501-6 :	Fca
Applicable standards :	ISO/IEC 11801 2nd ed., IEC 61156-5 EN 50173-1 EN 50288-6-1 ANSI/TIA-568.2-D EU Declaration of Conformity LVD Low Voltage Directive 2014/35/EC RoHS EC Directive 2015/863/EU

Wiring diagram

