



HIRSCHMANN

A BELDEN BRAND

Product information Compact OpenRail Fast Ethernet Switch 4-25 ports - RS20-0800M2M2SDHEHH06.0.

Industrial Ethernet:Archive - Industrial Ethernet:Compact configurable managed switches:with Firmware Release 6:Compact OpenRail Fast Ethernet Switch 4-25 ports

<http://e-catalog.hirschmann.com/link/57078-24455-49814-49854-173492-173497/en/RS20-0800M2M2SDHEHH06.0./uistate>

Name		Compact OpenRail Fast Ethernet Switch 4-25 ports
		
		8 port Fast-Ethernet-Switch, managed, software Layer 2 Enhanced, for DIN rail store-and-forward-switching, fanless design
Delivery informations		
Availability		available
Product description		
Description		8 port Fast-Ethernet-Switch, managed, software Layer 2 Enhanced, for DIN rail store-and-forward-switching, fanless design
Port type and quantity		8 ports in total; 1. uplink: 100BASE-FX, MM-SC; 2. uplink: 100BASE-FX, MM-SC; 6 x standard 10/100 BASE TX, RJ45
Type		RS20-0800M2M2SDHEHH06.0.
Order No.		943 434-015
New version available		Click here for the latest version
More interfaces		
Power supply/signaling contact		1 x plug-in terminal block, 6-pin
V.24 interface		1 x RJ11 socket
USB interface		1 x USB to connect the AutoConfiguration Adapter ACA21-USB
Network size - length of cable		
Multimode fiber (MM) 50/125 µm		0 - 5000 m, 8 dB link budget at 1300 nm, A = 1 dB/km, 3 dB reserve, B = 800 MHz x km
Multimode fiber (MM) 62.5/125 µm		0 - 4000 m, 11 dB link budget at 1300 nm, A = 1 dB/km, 3 dB reserve, B = 500 MHz x km
Network size - cascadiability		
Line - / star topology		any
Ring structure (HIPER-Ring) quantity switches		50 (reconfiguration time < 0.3 sec.)
Power requirements		
Operating voltage		12/24/48 V DC (9,6-60) V and 24 V AC (18-30) V (redundant)
Current consumption at 24 V DC		321 mA
Current consumption at 48 V DC		161 mA
Power output in Btu (IT) h		26.3
Software		
Management		Serial interface, web interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP
Diagnostics		LEDs, log-file, syslog, signal contact, RMON (statistic, history, alarms, events), port mirroring, topology discovery 802.1AB
Configuration		Command Line Interface (CLI), TELNET, BootP, DHCP, DHCP Option 82, HiDiscovery, auto-configuration adapter (ACA11, ACA21-USB), watchdog configuration
Security		Port Security (IP und MAC) with multiple addresses, SNMP V3 (no encryption)
Redundancy functions		HIPER-ring (ring structure), MRP (IEC-ring functionality), RSTP 802.1D-2004, redundant network/ring coupling, MRP and RSTP in parallel, redundant 24 V power supply
Filter		QoS 4 classes, port prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), shared VLAN learning, multicast (IGMP Snooping/Querier), multicast detection unknown multicast, broadcastlimiter, fast aging
Industrial Profiles		EtherNet/IP and PROFINET (2.2 PDEV, GSDML stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix
Time synchronisation		SNTP client/server, PTP / IEEE 1588
Flow control		Flow control 802.3x, port priority 802.1D/p, priority (TOS/DIFFSERV)
Presettings		Standard
Ambient conditions		
Operating temperature		0 °C ... 60 °C
Storage/transport temperature		-40 °C ... 70 °C
Relative humidity (non-condensing)		10 % ... 95 %
MTBF		53.5 years (MIL-HDBK-217F)

Industrial Ethernet:Archive - Industrial Ethernet:Compact configurable managed switches:with Firmware Release 6:Compact OpenRail Fast Ethernet Switch 4-25 ports
<http://e-catalog.hirschmann.com/link/57078-24455-49814-49854-173492-173497/en/RS20-0800M2M2SDHEHH06.0./uistate>

Protective paint on PCB	No
Mechanical construction	
Dimensions (W x H x D)	74 mm x 131 mm x 111 mm
Mounting	DIN Rail
Weight	410 g
Protection class	IP20
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7 g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	6 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80-1000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 1 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line
EN 61000-4-6 conducted immunity	3 V (10 kHz-150 kHz), 10 V (150 kHz-80 MHz)
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Hazardous locations	ISA 12.12.01 Class 1 Div. 2
Shipbuilding	Germanischer Lloyd
Railway norm	EN50121-4
Substation	IEC 61850-3, IEEE 1613
Scope of delivery and accessories	
Scope of delivery	Device, terminal block, operating manual

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.