HIRSCHMANN

MULTIMEDIA



MULTISWITCH 9 IN, 12 OUT TMS 9X12P

TMS 9XP multiswitches offer a flexible and cost efficient system for providing two position satellite distribution in small and medium sized networks. The systems uniqueness in design and performance makes community networks attractive even in buildings with only 2 or 3 households. 8 satellite polarities and 1 terrestrial input, 12 combined outputs. Also available in versions for 6, 8 and 12 subscriber outputs. Low power consumption. The TMP 9xP has an integrated power supply with grounding possibility.

Properties 2 Year Warranty Digital & 3D ready Low Power Power	Certificates	Included N/A
Instruction video www.hirschmann-multimedia.net/ montagefilm	Instruction card www.hirschmann-multimedia.net/ installation/installatie-schema	
Productsheet TMS 9X12P	Article number 100300342	Version 11.2014-1.0 Page 1 / 2

WWW.HIRSCHMANN-MULTIMEDIA.NET

Mechanical Specifications

Dimensions hxwxd 103 x 71 x 459 mm

Weight 1.7 kg

Color White

Specifications

Number of inputs
Subscriber outputs
Connectors
Frequency range SAT
Frequency range TER
Gain SAT
Gain TER
Isolation TER to SAT
Isolation SAT to TER
Isolation cross polarisation H/V
Isolation out - out TER
Isolation out - out SAT
Return loss SAT inputs
Return loss SAT outputs
Return loss TER inputs
Return loss TER outputs
Max. output level SAT (IMD-35 dB)
Max. output level TER (IMD-65 dB)
Impedance input/output
Switching

Supply voltage

Power supply LNB power supply max. Colourcoding of IF and TER inputs Temperature range

Contact

	Pampuslaan 170 1382 JS WEESP
\searrow	info@hirschmann.nl
s.	NL 31 (0)294 46 25 55 BE 32 (0)2 46 13 095
in	www.linkedin.com/company/hirschmann-multimedia-b.v.
f	www.facebook.com/hirschmann.multimedia
	www.youtube.com/HirschmannMultimedia

Productsheet TMS 9X12P


PRODUCTSHEET

TMS 9X12P

MULTISWITCH 9 IN, 12 OUT

8 SAT, 1 TER 12
F female
950-2150 MHz
47-862 MHz
0 dB
4 dB
30 dB
30 dB
25 dB
28 dB
30 dB
10 dB
10 dB
12 dB
10 dB
100 dBµV
83 dBµV
75 Ohm
13 V - 18 V
13 V/22 kHz -
18 V/22 kHz
DiSEqC 2.0
15 VDC (± 0.5)
(via DC plug or trunk)
Included
1000 mA
Yes
0- +55 °C

Wiring diagram



Related product - KOKA 799 BLACK

Article number 198799102

Related product - TMS 9 AMP

Article number 100300365



Related product - 2600S LINE AMP

Article number 100300401



Hirschmann Multimedia B.V.

Hirschmann Multimedia B.V. is an international knowledge company and manufacturer, located in Weesp -The Netherlands. Hirschmann Multimedia focusses on leading the market by being innovative, flexible and renewing.

Hirschmann Multimedia Products (HMP): Serving the retail and installer market, Hirschmann Multimedia Products is expanding from The Netherlands and Belgium towards 16 other European countries as of 2014. Through a qualified and selected dealer and installer network, HMP provides in products for COAX, IP and satellite systems.

Version 11.2014-1.0

Page 2/2

© Copyright 2014 Hirschmann Multimedia B.V. All rights reserved. This document is for informational purposes only. Specifications and features can be subject to change without notice. Company name Hirschmann Multimedia B.V. and trade marks are registered in The Netherlands and Europe. For general terms and conditions of sale and delivery: www.hirschmann-multimedia.net.

Article number 100300342

WWW.HIRSCHMANN-MULTIMEDIA.NET