

INDOOR COAX CABLE



KOKA TRI 11 B2ca/500 m

Article number 298799719


PRODUCT CATEGORY: CATV
STATUS: AVAILABLE



Product

INDOOR COAX CABLE
KOKA TRI 11 B2ca

Unarmoured Coax cable for indoor use for very large distances. This cable is suitable for use in medium and large building-related CATV systems. Class A++ screening. Large distances can be bridged by the low attenuation. This cable is particularly suitable for indoor use. Very high CPR classification: B2ca s1,d0,a1



Properties

2 Year Warranty	Screening Class >A++	3GHz Ready
High Durability	4G/LTE Proof	Digital & 3D Ready
Low Loss	B2ca s1 d0 a1	

Certificates



Included

N/A

Tools

N/A

Instruction video

N/A

Instruction card

N/A

Mechanical Specifications

Dimensions hwxwx
390 x 290 mm

Weight
57,0 kg

Color
White

PRODUCTSHEET

KOKA TRI 11 B2ca/500 m

INDOOR
COAX CABLE

Specifications

Application

75 Ohm coaxial cable used in indoor application, HFC/CATV signal distribution

Structural specifications

Inner conductor Bare copper wire, diameter 1.63 mm.
Dielectric Foamed PE with gas injection, diameter 7.1 mm
Outer shield Al-Pet-Sy foil, 27x0,08mm, bonded, diameter 7,40 mm
Tinned copper braid, 77% coverage, diameter 7,8 mm
Al-Pet foil, 30x0,03mm, bonded.
Sheath FRNC white, diameter 10 mm, ovality 4%
Compliant EN 50290-2-27 70°C

CPR Euroclass **B2ca s1,d0,a1**

Mechanical specifications

Operation temperature -40 °C to +70 °C
Min installation temperature -5 °C
Bending radius 60 mm
Max pulling tension > 300 N

Electrical specifications

Impedance 75 Ohm
Capacitance 50 pF/m
Velocity ratio 82%
DC Resistance < 8,7 Ohm/km

Attenuation

230 MHz 6 dB/100m
900 MHz 13 dB/100m

Screening attenuation

5-30 MHz < 0.9 mOhm/m
30-1.000 MHz > 105 dB
1000-2000 MHz > 95 dB
2000-3000 MHz > 85 dB


Return loss

5-470 MHz > 23 dB
470-1000 MHz > 20 dB
1000-1200 MHz > 18 dB

Wiring diagram

BENDRADIUS

rayon de courbure



Related product -

FM-RG11-CX3 10.5



Article number 695020531

Related product - GHV 51M



Article number 695021020

Related product -

F-59-CX3 6.0



Article number 695020530

Contact

📍 Pampuslaan 170
1382 JS WEESP

✉ info@hirschmann.nl

☎ NL 31 (0)294 46 25 55
BE 32 (0)2 46 13 095

🌐 www.linkedin.com/company/hirschmann-multimedia

📘 www.facebook.com/hirschmann.multimedia

📺 www.youtube.com/HirschmannMultimedia

Hirschmann Multimedia B.V.

Hirschmann Multimedia B.V. is an international knowledge company and manufacturer, located in Weesp - The Netherlands. Hirschmann Multimedia focusses on leading the market by being innovative, flexible and renewing.

Hirschmann Multimedia Products (HMP):

Serving the retail and installer market, Hirschmann Multimedia Products is expanding from The Netherlands and Belgium towards 16 other European countries as of 2014. Through a qualified and selected dealer and installer network, HMP provides in products for COAX, IP and satellite systems.